

# Bedford Tile

11.2013

TECHN. INFO	TECHN. DATEN	CAR. TECHN.	TECHN. GEGEV.	NORM	
Manufacturing process	Herstellungsart	Techn. de fabrication	Productiemethode	DIN61151	needle-felt
Surface aspect	Oberflächenstruktur	Aspect du surface	Poolstructuur		ribbed
Tile composition	Polmaterial	Comp. du poil	Poolmateriaal		100 % polyprop.
Tile weight	Polgewicht	Poids des fibres	Poolgewicht	ISO8543	900 gr/m <sup>2</sup> ± 10%
Tile height	Polhöhe	Hauteur velours	Poolhoogte		3,5 mm ± 10%
Prim. backing	Prim. Rückenbeschichtung	Dossier prim.	Prim. backing	ISO2424	styr. but. latex
Sec. backing	Sec. Rückenbeschichtung	Dossier sec.	Sec. backing	ISO2424	bitumen
Total height	Gesamthöhe	Hauteur tot.	Totale hoogte	ISO1765	8 mm ± 10%
Permanently antistatic	Permanent Antistatisch	Antistatique permanent	Permanent antistatisch	ISO6356	
Wear/abrading	Reibechtheit	Res. au frottement	Wrijfechtheid	ISO105X12	4 (except for 3342,3353:3)
Classification	Klassifikation	Classification	Classificatie	EN 13297	
Flammability	Brennklasse	Comportement au feu	Brandgedrag	EN 13501-1 BS 4790	efl-fully adhesive low
Intended use	Anwendung	Application	Toepassing		commercial
Acoustical impact	Trittschalldämmung	Performances acoustiques	Akoestische impact	EN ISO 140-8	24 db

Width: 0,5 m • Length: 0,5 m • Length: 0,5 m • Length: 0,5 m  
 Minimum order quantity 0,5 x 0,5 m tiles = 1 box with 16 tiles = 4 m<sup>2</sup>  
 Minimum order quantity 1 x 1 m tiles = 50 tiles = 50 m<sup>2</sup>

Due to limitations of the manufacturing process, colour may slightly vary from batch to batch.  
 We reserve the right to alter technical specifications.

Wegen dem Produktions Prozess bedingt, können geringe Farbabweichungen von Partie zu Partie auftreten. Wir behalten uns das Recht um die Technischen Daten zu ändern.

En raison des limitations de production, les coloris peut varier légèrement d'une production à l'autre. Le fabricant se réserve le droit de modifier les caractéristiques techniques.

Wegen beperkingen in het productieproces, zijn geringe Kleurafwijkingen van partij tot partij mogelijk. We behouden het recht de technische gegevens aan te passen.

## General Information

Before installation, check that all rolls or tiles are from the same dye batch number. All floor surfaces should be clean, dry and free from all dust and debris. All traces of old floor coverings should be removed. Tiles may only be installed over parquet or quarry tiled floors provided that there is an efficient damp proof membrane. This is because of moisture, which is prevented by the carpet tiles in dissipating, may cause the parquet or quarry to lift.

## Laying Instructions

It is recommended that the carpet be fully adhered directly to the sub-floor, which should be clean, level, and using a proprietary adhesive (see Ball F3/F4). For tiles adhesives must be non-solvent based and in the case of vinyl floor surfaces, adhesives must be compatible.

## Laying Directions

Notes: All adjacent pieces must be laid in the same direction. Tiles: Lay the tiles with the arrows on the back of adjacent tiles at right angles to achieve a chequerboard effect. Push each tile firmly against its neighbour. Contrasting or co-ordinating colours may be used to build up your own design.



## Cutting

Cut with a Stanley knife or similar, preferably from the back, then part the surface pile.

## Maintenance

Regular daily suction vacuum cleaning (diagonally for tiles) and occasional hot water extraction is recommended. Most stains can be removed by a good quality purpose made chemical. Do not use oil or any similar product. Traffic paths may be avoided by periodically interchanging the tiles. It is strongly recommended that a protecting mat or similar is used under castor chairs. Colours may vary from those shown on the sampling due to the manufacturing process. No claims will be considered as a result of improper application, installation or maintenance. Pile pressure marks, staining and soiling are not manufacturing defects.



BQA\_QMS019\_C\_199658